

Electric and Manual Beds

Designed to
Simplify Patient Care



Manual

Electric

The Stryker Electric and Manual Med/Surg beds address the demands put on today's nursing professional.

Keeping our product design focused on key needs ensures a practical, economical and user-friendly platform. Safety features such as low bed height and ergo siderails combined with convenience features, which include centrally located lock and steer system, increase comfort for patients and help relieve strain on caregivers.



Optional Ergo Siderails



Low Bed Height



Siderail Control Panel

Choice of Ergo, full- or half-length siderails in chrome or painted finish

Centrally located **lock and steer system**

Optional **fixed patient siderail controls**

Fifth wheel helps improve maneuverability and ease transport

Battery backup for continued power during transport

Electric and Manual Beds



Electric



Manual

Standard Features

- 6-inch (15 cm) casters
- Centrally located lock and steer system
- Two drainage bag hooks
- Eight IV pole and traction equipment sockets
- Patient restraint locations
- Lateral and foot end mattress retainers
- Trend. / Reverse Trend. controls
- Half-length siderails
- Painted siderail finish
- Battery backup

Optional Features Electric

- PVC siderail protector
- Oxygen bottle holder
- Patient helper
- Monitor tray
- Retractable fifth-wheel steering
- Auto contour
- Foot board controls
- Bed flat button
- 4 wheel brake system
- Ergo siderail
- 5-inch caster providing a 12-inch low bed height
- Angle Meter on siderail (painted Ergo siderail only)
- CPR release
- Night light
- Nurse call
- Full length siderails
- Roller bumpers at head end of bed
- Chrome finished siderails

Optional Features Manual

- PVC siderail protector
- Removable crank handle
- Oxygen bottle holder
- Patient helper
- Monitor tray
- Retractable fifth-wheel steering
- Stabilizer Legs
- Permanent head and footboards

Specifications

| | Electric | Manual |
|------------------------------------|-------------------------|-------------------------|
| Model Number | FL23SE | FL23SM |
| Overall Length | 88.5" (224.8 cm) | 88.5" (224.8 cm) |
| Overall Length with Roller Bumpers | 90.5" (229.8 cm) | 90.5" (229.8 cm) |
| Overall Width | 41.5" (105.4 cm) | 41.5" (105.4 cm) |
| Weight Capacity | 500 lb. (227 kg) | 500 lb. (227 kg) |
| Height Range (to litter top) | | |
| High | 31" (78.8 cm) | 29" (73.7 cm) |
| Low | 13" (33 cm) | 15" (38.1 cm) |
| Litter Positioning | | |
| Backrest | 0°–60° | 0°–62° |
| Knee Gatch | 0°–25° | 0°–32° |
| Trend. / Reverse Trend. | ±12° | ±14° |
| Patient Surface | 35" x 78" (89 x 198 cm) | 35" x 78" (89 x 198 cm) |
| | 35" x 80" (89 x 203 cm) | 35" x 80" (89 x 203 cm) |
| Caster Diameter (standard) | 6" (15 cm) | 6" (15 cm) |

Electronics

| | |
|---------------------|---|
| Agency Approvals | C-US CSA |
| Volts | 120 V AC (Domestic) / 220-230-240 V AC |
| Ampere Rating | 4 A (Domestic) / 2.0 A (International) |
| Current Leakage | < 300 microamperes |
| Frequency | 60 Hz (Domestic), 50 Hz (International) |
| Hospital Grade Plug | Yes |
| Battery Type | 24 V Lead Acid 1.2Ah |

Stryker reserves the right to change specifications without notice.